

ExxonMobil Petroleum & Chemical BV CERTIFICATE OF ANALYSIS

Customer Product Name:

Product Name/Grade: **JAYFLEX DIUP**

Date Printed: 31 MAR 2021

Railcar/ Vessel/Truck #:

Compartment #: 1

ANALYSIS				
Property	UoM	Results	Specifications	Test Method
Ester Content	wt%	99,9	>= 99,7	RPP 201
Water Content	wt%	0,02	<= 0,05	ISO 12937
ACID VALUE	mg/g	0,03	<= 0,07	ASTM D1045
COLOR, Pt-Co	Pt/Co	6	<= 30	ASTM D5386
DENSITY 20C	g/cm3	0,9605	0,9590 - 0,9630	ASTM D4052
DYN. VISCOSITY , 20 C	mPa.s	147	135 - 165	ASTM D445
REFRACTIVE INDEX, 20 oC		1,4849	1,4840 - 1,4870	ASTM D1218

Reported decimal places may differ from what is specified in industry standard test method

Unless otherwise specified herein: data were prepared pursuant to ExxonMobil's sampling and testing procedures in effect at time of production; and applicable sampling and testing methods are available upon request. Values may result from interpolation or correlation of other data. Sampling and testing methods are subject to change without notice unless otherwise agreed in writing.